


BOMAG

TANDEM VIBRATORY ROLLERS BW 100 AD-4, BW 120 AD-4, BW 125 AD-4

PERFORMANCE DATA



Machine type	Compaction output (m ³ /h) at recommended soil layer thicknesses		
	Gravel, sand	Mixed soil	Silt, clay
BW 100 AD-4	80-145	55-105	38-73
BW 120 AD-4	85-170	65-125	43-85
BW 125 AD-4	90-185	70-140	50-95


Machine type	Compaction output (t/h) at different asphalt layer thicknesses		
	2-4 cm	6-8 cm	10-12 cm
BW 100 AD-4	15-40	40-60	60-100
BW 120 AD-4	20-45	40-70	70-120
BW 125 AD-4	25-50	45-80	75-130

BOMAG

Technical Data

Shipping dimensions in m3

	without ROPS	with ROPS
BW 100 AD-4	4,794	6,591
BW 120 AD-4	5,685	7,816
BW 125 AD-4	5,685	7,816



Standard Equipment

- Oscillating artic. center joint
- 2 scrapers per drum
- Suspended operator's platform
- Plastic water tank
- Hour meter
- Lockable engine cover
- Lockable anti vandal dashboard protection
- Transport lashing and lifting points front/rear
- Emergency stop button
- Vibration cut-off, rear drum
- Back-up alarm
- Water level
- Gravity water sprinkler system

Optional Equipment

- * ROPS with safety belts
- * Working lights front/rear
- * Seat with contact switch
- Edge cutter
- Indicator and hazard lights
- Rotary beacon
- Biodegradable hydraulic oil
- Special paint
- Tool kit
- Double travel lever (Sliding seat)
- Foldable ROPS
- Laterally sliding seat
- Fuel level indicator
- Single point lifting device
- Pressure sprinkler system
- Electronic Engine Immobilizer
- Weather protection cabin
- Battery disconnect switch
- Document bag
- Sun roof
- Flow divider

* Standard delivery with CE conformity (valid within European Union)

Dimensions in mm

	A	B	C	D	H	H2	K	L	O	S	W
BW 100 AD-4	1728	1076	475	700	1800	2475	255	2475	38	13	1000
BW 120 AD-4	1728	1276	474	700	1800	2475	255	2475	38	13	1200
BW 125 AD-4	1728	1276	474	700	1800	2475	255	2475	38	23	1200

Technical Data

	BOMAG BW 100 AD-4	BOMAG BW 120 AD-4	BOMAG BW 125 AD-4
Weights			
Operating weight w. ROPS CECE	kg 2.400	2.600	3.150
Average axle load CECE	kg 1.200	1.300	1.575
Average static linear load CECE	kg/cm 12	10,8	13,1
Dimensions			
Length with ROPS	mm 2.475	2.475	2.475
Track radius, inner	mm 2.720	2.620	2.620
Driving Characteristics			
Max. working speed with vibration	km/h 0- 6,5	0- 6,5	0- 6,5
Max. travel speed	km/h 0- 12,0	0- 12,0	0- 12,0
Max. gradeability without/with vibr.	% 40/30	40/30	40/30
Drive			
Engine manufacturer	Kubota	Kubota	Kubota
Type	D1703-M-EU32	D1703-M-EU32	D1703-M-EU32
Cooling	water	water	water
Number of cylinders	3	3	3
Performance ISO 9249	kW 24,7	24,7	24,7
Performance SAE J 1349	hp 33,1	33,1	33,1
Speed	min-1 2.600	2.600	2.600
Speed adjustment 1	min-1 2.400	2.400	2.400
Speed adjustment 2	min-1 2.600	2.600	2.600
Electric equipment	V 12	12	12
Brakes			
Service brake	hydrost.	hydrost.	hydrost.
Parking brake	hydromec.	hydromec.	hydromec.
Steering			
Steering system	oscil.artic.	oscil.artic.	oscil.artic.
Steering method	hydrost.	hydrost.	hydrost.
Steering angle +/-	grad 30	30	30
Oscillating angle +/-	grad 7	7	7
Exciter system			
Vibrating drum	front + rear	front + rear	front + rear
Drive system	hydrost.	hydrost.	hydrost.
Frequency	Hz 70/55	70/55	60/50
Amplitude	mm 0,49	0,51	0,40
Centrifugal force	kN 37/23	45/28	41/29
Sprinkler System			
Type of sprinkling	gravity	gravity	gravity
Capacities			
Fuel	l 40	40	40
Water	l 220	220	220

Technical modifications reserved. Machines may be shown with options.



BOMAG
 Hellerwald
 D-56154 Boppard
 P.O. Box 5162
 Tel. (0)6742 - 1000
 Fax (0)6742 - 3090
 Fax (0)6742 - 3090

BOMAG